



New in the fleet!

165DT, 165D & 205D

Chippers



Stage V engine



Easy to transport

New in the fleet!

165DT, 165D & 205D Chippers

These chippers are equipped with Kubota Stage-V diesel engines and a blade system that requires little maintenance and shreds very nicely. There are handles on the sides of the wood chipper to make it easy to move.

The chippers are also equipped with a height-adjustable drawbar, folding discharge chimney and shielded lighting. They are easy to transport and can therefore be quickly deployed in multiple locations.



Stage V engine



Easily transportable

Technical data	165DT	165D	205D
Rental number	401616	401565	401590
Type	Tracked chassis	Trailer	Trailer
max. trunk diameter (mm)	165	165	205
Fuel	Diesel	Diesel	Diesel
Cutting blades	4	4	6
Cutting blade speed (per min)	1.380	1.380	1.580
Discharge chute	280° rotation	280° rotation	280° rotation
Ground pressure (kg/cm ²)	0,255	0,380	-
Ground clearance (mm)	194	-	-
Weight ± (kg)	1.410	1.000	1.450

Dimensions	165DT	165D	205D
Infeed chute aperture (mm)	1.200 x 700	1.200 x 700	1.300 x 840
Infeed throat size (mm)	220 x 165	220 x 165	270 x 205
Length (mm)	2.540	2.540	4.000
Width (mm)	1.370	1.370	1.600
Height (mm)	2.580	2.580	2.760

Engine	Stage V	Stage V	Stage V
Power (hp)	25	25	49,6
Type	Kubota Diesel	Kubota Diesel	Kubota Turbo-Diesel
Norm	Stage V	Stage V	Stage V
Tank capacity (l)	33	33	33



- ✔ Stage V engine
- ✔ Suitable for rough terrains
- ✔ Large entry
- ✔ Fast processing