



**WORKPLACE SAFETY
- A CHOICE FOR YOU
TO MAKE**



IXOLIFT 400

**THE SAFE AND
SMART ALTERNATIVE
TO LADDERS**

IXOLIFT®

IXOLIFT 400

ADJUSTABLE WORK PLATFORM

- Simple and safe to use
- Working height up to 4 meters
- Safety compliant alternative to ladders
- Compact sized, easy to move around alone
- Automatic anti-surfing brakes for extra safety
- Patented gas spring powered height adjustment
- Eco friendly, hydraulic oil free, maintenance free
- Options: ATEX rating, Stainless steel version



TECHNICAL SPECIFICATIONS	IXOLIFT 400W	IXOLIFT 400WS
Working height	3974 mm	
Max working load	150 kg	
Max platform height	1974 mm	
Min platform height	974 mm	
Platform size	526 x 556 mm	
Stowed height	1970 mm	
Stowed length	1198 mm	
Stowed width	728 mm	
Total weight	230 kg	
Max length with stabilisers out	N/A	1500 mm
Max width with stabilisers out	N/A	1668 mm
Wind rating	0 m/s	12,5 m/s
CE Marking	Machinery Directive 2006/42/EC EN 280:2013 + A1:2015 except §5.6.2 Guardrails based on EN 131-7 §5.6	
ATEX Marking (Optional)	ATEX Directive 2014/34/EU Ex h IIC T6 Gb & Ex h IIIC T60°C Db	

PATENTED



Compact size



Automatic brakes



Gas spring powered



Tool tray