



New in the fleet!

ROOF EDGE PROTECTION



Easy and fast (dis)assemble



Can be used up to wind force 5

00

Robust & durable construction



New in the fleet!

ROOF EDGE PROTECTION

Scaffolding material

This aluminum roof edge protection is quick to assemble, easy to use and makes a safe working environment of a flat roof. The roof edge protection can be extended per 3 metres.

The aluminum roof edge foot is made of a 3 mm thick profile: the perfect combination of weight and solidity.

RENTAL NUMBER





Easy and fast (dis)assemble



Can be used up to wind force 5



Robust & durable construction

Technical specs

| Length |
|----------------------|
| Max. load |
| Weight ballast block |

3,00 m 300 kg 22,5 kg

- ✓ Easy and quick to (dis)assemble
- Extendable per 3 meters
- ✓ 3mm profile
- Easy transport due to folding handrail holders
- ☑ Ballast blocks of B25 concrete mix with handles







Collé Rental & Sales Nusterweg 100-102 6136 KV Sittard The Netherlands

www.colle.eu info@colle.eu 00800 - 3625 3625



DISCLAIMER: No rights can be derived from the texts, specifications, images, or other information found in this flyer. Everything in this flyer is subject to change. Photographs, texts, and specifications are approximations and are non-binding. During the design and creation of this flyer, we worked as carefully as possible. However, we provide no guarantee that the information in this flyer is complete, current, and/or accurate.