

# IXOLIFT 500

## PUSH IT OR DRIVE IT HYBRID INVENTION

- 2 in 1 - switch to push around or self-propelled mode via the lever
- Simple - self-explanatory use without fear of contact
- Compact - easily passes through standardized doors, lifts and narrow aisles
- Light - low weight allows sole use
- High - reaches a working height of up to 4.95 metres



| TECHNICAL SPECIFICATIONS | IXOLIFT 500   |                 |
|--------------------------|---|-----------------|
| Working height           | 4.95 m  |                 |
| Max working load         | 180 kg  |                 |
| Max platform height      | 2.95 m  |                 |
| Platform size            | 0.53 x 0.76 m   |                 |
| Guardrail height         | 1.10 m  |                 |
| Transport height         | 1.64 m  |                 |
| Transport length         | 1.20 m  |                 |
| Transport width          | 0.76 m  |                 |
| Total weight             | 320 kg  |                 |
| Driving speed            | raised, 2 km/h  | lowered, 4 km/h |
| Power source             | 2 pc, 75 Ah, 12 V batteries, maintenance-free           |                 |
| Wheels                   | Polyurethane coating, leaves no marks                   |                 |
| CE Marking               | Machinery Directive 2006/42/EG<br>EN 280:2013 + A1:2015 |                 |



**Decoupling**



**USB Socket**



**Self-Propelled**



**Push Around**