## SCISSOR LIFT ES1218RT (2)



- ✓ 100% ELECTRIC
- ✓ DRIVE AT FULL HEIGHT
- ✓ 4X4 WHEEL DRIVE
- ✓ GRADEABILITY 40%
- ✓ EXTENSION DECK
- ✓ AUTOMATIC LEVELING
- ✓ SWING AXLE
- ✓ NON-MARKING TIRES

## **TECHNICAL SPECIFICATIONS**

Working height	12.00 m
Platform height	10.00 m
Length	3.84 m / 3.19 m
Width	1.76 m
Height (Rails up)	2.59 m
Height (Rails down)	1.82 m
Platform length x width	2.88 m x 1.52 m
Platform extension	1.43 m
Ground clearance	0.24 m
Wheelbase	2.29 m
Load capacity	454 kg
Load capacity on platform extension	136 kg
Max number of persons	4 Persons
Turning radius (inside / outside)	2.15 m / 4.85 m
Driving speed (retracted)	
Brining speed (retracted)	6.00 km/h
Driving speed (extended)	6.00 km/h 0.48 km/h
Driving speed (extended)	0.48 km/h
Driving speed (extended) Weight	0.48 km/h 4,400 kg
Driving speed (extended) Weight Motor	0.48 km/h 4,400 kg 2 x 32 VAC / 3.3 kW
Driving speed (extended) Weight Motor Hydraulic tank	0.48 km/h 4,400 kg 2 x 32 VAC / 3.3 kW 71 Liters
Driving speed (extended) Weight Motor Hydraulic tank Batteries	0.48 km/h 4,400 kg 2 x 32 VAC / 3.3 kW 71 Liters 8 x 6V / 315Ah







Disclaimer: No rights can be derived from the texts, specifications, images, or other information found in this data sheet. Everything in this data sheet is subject to change. Photographs, texts, and specifications are approximations and are non-binding. During the design and creation of this data sheet, we worked as carefully as possible. However, we provide no guarantee that the information in this data sheet is complete, current, and/or accurate.