

# Atlas Copco Generators

## Designed to perform, built to last



## QAS 20/25 (60 Hz)

With standard features that maximize safety and minimize environmental impact, the QAS 20/25 also features:

- Diesel power from the reliable Kubota engine
- Electrical power from Leroy Somer LSA series alternator
- Atlas Copco QC1002 control system
- 29 hours at 75% load fuel consumption

The QAS 20/25 line provides quieter operation, reduced emissions, and lower acquisition and operating costs.

[www.atlascopco.com/portablepower](http://www.atlascopco.com/portablepower)

*Sustainable Productivity*

*Atlas Copco*

# Technical Data

Model	QAS 20/25
Sound Pressure Level @ 23 feet @ 75% load	65 dB(A)
Fuel Tank Capacity	30 gal.
Fuel Consumption @ 75% load	1.04 gal/hr
Fuel Autonomy @ 75% load	29 hr

Engine	Kubota
Model	V2403
Rated Speed	1800 rpm
Emission Compliance	EPA IT4
Rated Output	29.6 HP @ 1800 rpm
Coolant	Water / Glycol
Cylinders	4
Displacement	2.4 L
Engine Control	Electronic

Alternator	Leroy Somer
Model	LSA40M5
Degree Of Protection / Insulation Class	IP23 / H

Dimensions and Weight	
Dimensions Skid (L x W x H)	82.5 x 37.4 x 51 in.
Weight - Skid Wet	1,868 lbs
Dimensions w/trailer (L x W x H)	110 x 59 x 57 in.
Weight - w/trailer Wet	2,121 lbs

Convenience Receptacles	
20 amp - 125 volt GFCI duplex	2
50 amp - 125 / 250 volt twist lock	2

The information contained herein is general in nature and is not intended for specific construction, installation or application purposes.

## Generator Features and Options Include

Multi-Voltage Selector Switch	•
Remote Start / Stop	•
Digital Control System	•
110% Fluid Containment	•
Electronic Governor	•
Skid-Mount	○
Battery Charger	○
Coolant Heater	○
Ball Coupling	○
Spare Tire	○
Rear Stabilizer Jacks	○
Tool Box	○
External Fuel Connections	○

Standard •  
Option ○

QAS 20	
Rated Standby Power	19.2 kW / 19.2 kVA
Rated Prime Power	17.3 kW / 17.3 kVA
Voltage Selections - 1Ø	120 / 240
Amperage Capacity @ 120 volts 1Ø	2 x 66 amps
Amperage Capacity @ 240 volts 1Ø	70 amps

QAS 25	
Rated Standby Power	22 kW / 22 kVA
Rated Prime Power	20 kW / 25 kVA
Voltage Selections - 3Ø	208/240/480
Amperage Capacity @ 208 volts 3Ø	69
Amperage Capacity @ 240 volts 3Ø	60
Amperage Capacity @ 480 volts 3Ø	30



## Control Panel

A comprehensive instrument panel enables all key operating functions to be supervised without opening the canopy. Analog gauges provide at-a-glance monitoring. Protected by a tough transparent cover, the single panel provides easy start up and control of the generator. The panel also provides full system monitoring to ease operation.

## Atlas Copco Construction Equipment

3700 East 68th Avenue  
Commerce City, CO 80022 USA  
Phone: +1 (303) 253-6922;  
Fax: +1 (303) 217-2840  
www.atlascopco.us



1310 9056-36 FAB 12/08 2M - Subject to modifications without prior notice.

# Sustainable Productivity

Use only authorized parts. Warranty or Product Liability does not cover any damage or malfunction caused by the use of unauthorized parts.

