

## 5075

Wheel Loaders 0.7 - 0.95 m<sup>3</sup>



# The down-to-earth performer

The new 5 Series models feature simple operation, compact design, and manoeuvrability. Even in the economy class, the rigid frame and all-wheel steering provide all the Kramer benefits such as constant payload, stability, and manoeuvrability.

- Undivided frame and all-wheel steering for constant payload and manoeuvrability
- The 5085T features a hydraulic quick-hitch system and a parallel loading system as well as Z-kinematics.
- Spacious newly developed cab with superb all-round visibility
- Efficient high-pressure drive system for low operating costs and high thrusting force
- · Diverse options provide versatility



# 5075

Wheel Loaders 0.7 - 0.95 m<sup>3</sup>

# **Technical specifications**

|               |            | g data |
|---------------|------------|--------|
|               |            |        |
| $\sim$ $\sim$ | O LOCK III | gaaco  |

| Bucket capacity (standard bucket) | 0.75 m³  |
|-----------------------------------|----------|
| Operating weight                  | 4,100 kg |

## Engine / Motor

| Engine / Motor manufacturer | Yanmar |
|-----------------------------|--------|
| Engine performance          | 35 kW  |

#### Power transmission

| Travel speed      | 20 km/h                   |
|-------------------|---------------------------|
| Differential lock | Self-locking differential |
| Standard tires    | 12.5–18                   |

## Steering and operating hydraulics

| Flow rate (pump)   | 52 l/min |
|--------------------|----------|
| Pressure (maximum) | 240 bar  |

## Kinematics

| Tipping load (with standard bucket) | 3,150 kg |
|-------------------------------------|----------|
| Payload (S = 1.25)                  | 1,900 kg |

Additional technical data is available in the detailed brochure within the information section



#### **Dimensions**



| Height                                | 2,450 mm |
|---------------------------------------|----------|
| Length                                | 5,080 mm |
| Width                                 | 1,720 mm |
| Ground clearance                      | 300 mm   |
| Wheelbase                             | 2,020 mm |
| Center of front axle to tip of teeth  | 1,570 mm |
| Center of rear axle to end of vehicle | 1,490 mm |
| Bucket width                          | 1,750 mm |
| Bucket pivot point                    | 3,065 mm |
| Overhead loading height               | 2,915 mm |
| Dumping height                        | 2,400 mm |
| Dump reach                            | 650 mm   |
| Stack height                          | 2,800 mm |
| Turning radius (above tyres)          | 2,840 mm |
|                                       |          |

#### Information on suitable accessories can be found on our website.

The right to make changes is reserved in the interests of ongoing further developments. You can find more information on the engine power in the operator's manual. The actual power output figures may vary due to specific operating conditions.

Information on suitable accessories can be found on our website. More detailed information on engine power can be found in the operator's manual; the stated power may vary due to specific operating conditions. Subject to alterations and errors excepted. Applicable also to illustrations. Copyright © 2015 Kramer-Werke GmbH.