

5095 Wheel Loaders 0.7 - 0.95 m³



The down-to-earth performer

The new 5 Series models feature simple operation, compact design, and manoeuvrability. Even in the economy class, the rigid frame and all-wheel steering provide all the Kramer benefits such as constant payload, stability, and manoeuvrability.

- Undivided frame and all-wheel steering for constant payload and manoeuvrability
- The 5085T features a hydraulic quick-hitch system and a parallel loading system as well as Z-kinematics.
- Spacious newly developed cab with superb all-round visibility
- Efficient high-pressure drive system for low operating costs and high thrusting force
- Diverse options provide versatility



5095 Wheel Loaders 0.7 - 0.95 m³

Technical specifications

0.95 m³
4,800 kg
Kohler
55.4 kW
20 km/h
30 km/h
100% connectable
12.5–20
70 l/min
240 bar
3,700 kg
2,300 kg

Additional technical data is available in the detailed brochure within the information section



Dimensions

×

Height	2,480 mm
Length	5,410 mm
Width	1,720 mm
Ground clearance	330 mm
Wheelbase	2,020 mm
Center of front axle to tip of teeth	1,900 mm
Center of rear axle to end of vehicle	1,490 mm
Bucket width	1,950 mm
Bucket pivot point	3,290 mm
Overhead loading height	3,090 mm
Dumping height	2,580 mm
Dump reach	650 mm
Stack height	3,040 mm
Turning radius (above tyres)	2,840 mm

Information on suitable accessories can be found on our website.

The right to make changes is reserved in the interests of ongoing further developments. You can find more information on the engine power in the operator's manual. The actual power output figures may vary due to specific operating conditions.

Information on suitable accessories can be found on our website. More detailed information on engine power can be found in the operator's manual; the stated power may vary due to specific operating conditions. Subject to alterations and errors excepted. Applicable also to illustrations. Copyright © 2015 Kramer-Werke GmbH.