

HY-BRID LIFTS™
BY CUSTOM EQUIPMENT INC



HB-P5.0

PUSH-AROUND AERIAL WORK PLATFORM

FEATURES & SPECIFICATIONS

HB-P5.0

INCREASED WORK SITE SAFETY

Sturdy and easy to operate Hy-Brid Lifts are the safe and efficient alternative to ladders or scaffolding on a job site.

COMPACT DESIGN

The HB-P5.0 is 70 cm wide and can easily maneuver through doors and onto standard personnel elevators.

MAINTENANCE FREE

Maintenance free AGM Battery and easy access panels improve life cycle and cost of ownership.

LOW FLOOR LOADING

Extremely lightweight design makes the lift easy to push around and allows for use on delicate or sensitive surfaces.

USER-FRIENDLY DESIGN

Low step height and full swing gate provide easy access to platform and reduce chances of knee and neck strain.

ROBUST RAIL SYSTEM

Unique rail technology provides greater durability and resilience against wear on the job site.

OVERSIZED 3.18 CM PINS

Robust scissor stack requires no greasing and oversized pins reduce scissor sway.

INTEGRATED HYDRAULIC SYSTEM

Pump and cylinder system are integrated providing less potential leak points.

TOTAL-LOCK REAR CASTERS

Prevents unwanted wheel and caster rotation

AUTO-LOCK BRAKES ON FRONT TIRES

Prevents machine surfing during use.

NON-MARKING WHEELS

Protect sensitive floors and prevent surface scuffs on job site.



HEIGHTS

| | |
|--------------------------|---------|
| Working Height | 4.95 m |
| Platform Height Max | 2.95 m |
| Platform Height Min | 70.6 cm |
| Ground Clearance Lowered | 4.1 cm |

METRIC

MEASUREMENTS

| | |
|-----------------|----------|
| Overall Length | 109.2 cm |
| Overall Width | 70 cm |
| Stowed Height | 180.6 cm |
| Platform Length | 94 cm |
| Platform Width | 55.9 cm |

PERFORMANCE

| | |
|--------------------|--------------|
| Platform Capacity | 249.5 kg |
| Rated Occupancy | 1 person |
| Weight | 394.9 kg |
| Lift Speed Up/Down | 16/14 sec |
| Power Source | 12V DC |
| Tires Front/Rear | 20.3/20.3 cm |

FLOOR LOADING

| | |
|------------------|------------|
| Min Wheel Load | 1415.5 kPa |
| Max Wheel Load | 2816.5 kPa |
| Min Machine Load | 6.2 kPa |
| Max Machine Load | 10.1 kPa |

1-866-334-0756 // WWW.HYBRIDLIFTS.COM

This brochure is for illustrative purposes only and based on the latest information available at the time of printing. Hy-Brid Lifts reserves the right to make changes at any time, without notice, to specifications, standard and optional equipment. Hy-Brid Lifts™ is a trademark of Custom Equipment, Inc. ©2016 Custom Equipment, Inc. All rights reserved.
01/16 Part No. L01-10

HY-BRID LIFTS™
BY CUSTOM EQUIPMENT INC.